



## Model Name

**BH280 Digital Signage**

## Unique selling point

- \* Landscape & Portrait orientation mode support
- \* Ultra wide aspect ratio
- \* High Brightness

<b>Panel</b>	<b>Screen Diagonal</b>	28"	
	<b>Backlight</b>	Edge LED	
	<b>Resolution</b>	1920 x 358 (pixels)	
	<b>Aspect Ratio</b>	16:3	
	<b>Brightness</b>	700 nits	
	<b>Contrast Ratio</b>	3000:1	
	<b>Viewing Angle</b>	178° (CR>20)	
	<b>Color gamut (x% NTSC)</b>	72%	
	<b>Frame Rate</b>	60%	
	<b>Response Time</b>	6ms	
	<b>Panel bit</b>	8 bit	
	<b>Light life</b>	50,000 hrs (typ.)	
	<b>Orientation</b>	Landscape / Portrait	
	<b>Interface</b>	<b>Input/Output</b>	Power (DC) In/ Out
Audio line-out			x 1
Composite video In/ Out (BNC)			NA
Composite audio In/ Out (RCA)			NA
Component video (RCA)			NA
External Speaker Out (L/R)			NA
D-sub In/ Out			x 1/ NA
HDMI (Type A )			NA
DVI-D In/ Out			x 1(DVI compatible with HDMI)/ NA
DisplayPort Input			NA
RJ45			NA
RS232 In/ Out			x 1
USB			NA
<b>Others</b>		AC power switch	NA
<b>Mechanical</b>	<b>Dimensions(W x H x D)</b>	736.6 (W)x 167.3 (H)x 43.6(D) (mm)	
	<b>Bezel Width (T/B/L/R)</b>	16.9/18.6/18.5/18.5 mm	
	<b>Weight (without packing /</b>	3 / 6.5 kg	
<b>Power</b>	<b>Power supply</b>	100 V ~ 240 V, 50 Hz / 60 Hz	
	<b>Power consumption</b>	40W (ON) Typ.	
<b>OSD</b>	<b>On-Screen Display</b>	EN/TC/SC (3 Languages)	
<b>Software</b>	<b>Color Calibration</b>	NA	
	<b>Multiple Display Control</b>	NA	
<b>Accessories</b>	<b>Standard</b>	Remote Control w/ Battery	NA
		Power Cord (by region)	x 1
		Quick Start Guide	NA
		IR Extender Cables	NA
		VGA(D-sub 15pin) Cable	NA
		RS232 Cable	NA
	<b>Optional</b>	Stand	NA
		Edge Finishing Kits	NA
		i1 Display PRO color meter (for Color Calibration SW)	NA

# BH280 Digital Signage

## 28" Dimension

