


Model Name


RP790 IFP

Unique selling point

- * IR 10-points Multi-touch (up to 10 points)
 * Touch Driver Free/ Multi-Platform Support
- * Closed Android System/Build-in Annotation SW * Anti-Glare/ Eye Care Mode with TUV Certification * Input Source with Touch enable

" input Sou	rce with Touch enable	T		
Panel	Screen Diagonal	79"		
	Backlight	LED	LED	
	Resolution	3840 x 2160		
	Aspect Ratio	16:9	16:9	
	Brightness	400nits		
	Contrast Ratio	1200:1		
	Viewing Angle	178 degree (H) / 178 degree (V)		
	Color gamut (x% NTSC)	72%		
	Frame Rate	120Hz		
	Response Time	5ms		
	Panel bit	10-bit		
	Light life	30000hrs		
	Orientation	Landscape		
Touch solution	Touch tech.	IR		
	Number of touches	Multi-touch up to 10 touches (varies from operating systems and applications)		
	Touch interface	USB (Type A) x 2		
Cover glass	Resolution	32767 × 32767		
	Thickness	Tempered, 4 mm		
	Hardness	7H		
	AG coating	80%		
Speaker	Built-in speaker	10W x 2		
орешке	Zane in speake.	Power (AC) Inlet	x I	
Interface	Input	Audio line-in	x I	
			x I	
		Composite video		
		Composite audio(L/R RCA)	x I	
		D-sub	xI	
		Type A HDMI	x 5 (HDMI I.3 x 3; HDMI I.4 x2)	
		USB port (for USB playback)	x 2	
		USB port (USB extender)	x 2 (for OPS)	
		RS232	x I	
		OPS	x l	
		LAN	x I	
		MIC	x I	
		Component video (YPbPr)	x I	
	Output	Composite video	x I	
		Composite audio(L/R RCA)	x I	
		Type A HDMI	x I (HDMI I.3)	
		RS232	x I	
		COAX	x I	
			x 2	
		Earphone		
		IR receiver	x	
Mechanical	Dimensions(W x H x D)	1847 * 1093 * 95 mm/2115 * 1400* 360 mm		
	Weight	87kg/112kg		
Power	Power supply	AC100 to 240V, 50 to 60 Hz		
	Power consumption	<250W		
OSD	On-Screen Display Languages	EN/EF/SP/EP/CN/TC/GM/DT/PL/RS/CZ/DN/SW/IT/RM/FN/NG/GK/TK/AB/JP (21L)		
Accessories	Standard	Remote Control w/ Battery x I		
		Power Cord (by region)	x 5	
		Touch pen	x 2	
		Quick Start Guide	x I	
		Pen Tray	x I	
		Touch Cable (USB to USB)	x I	
		VGA(D-sub 15pin) Cable	x I	
		Wall mount	N/A	
		an mount		





Dimension

